

"Express Mail" mailing label number EH862489475US

Date of Deposit Dec 13, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" services under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Typed Name of Person Mailing Paper or Fee: Terri Walker

Signature: Terri Walker

PATENT APPLICATION
DOCKET NO. 10003222-1

**IMAGE FORMING DEVICES AND METHODS OF FACILITATING
ORDERING OF AN IMAGING CONSUMABLE**

INVENTORS:

Robert E. Haines

Mark A. Harper

DOCKET 10003222-1

FIELD OF THE INVENTION

10

15

20

25

30

SUMMARY OF THE INVENTION

The invention provides image forming devices and methods of facilitating ordering of an imaging consumable.

According to one aspect, an image forming device includes an interface
5 adapted to communicate with a communication medium external of the image forming device; imaging circuitry configured to use an imaging consumable to form hard images; a sensor configured to monitor a status of the imaging consumable; and processing circuitry coupled with the sensor and configured to generate a message indicating the status of the imaging consumable and to synchronize with
10 another image forming device to control a timing of a communication of the message externally of the image forming device using the interface.

A second aspect of the invention provides a image forming device comprising: an interface adapted to communicate with a communication medium external of the image forming device; imaging circuitry configured to use an
15 imaging consumable to form hard images; a sensor configured to monitor a status of the imaging consumable; and processing circuitry coupled with the sensor and configured to generate a message indicating the status of the imaging consumable and to communicate the message externally of the image forming device using the interface at a predetermined moment in time.

Another aspect of the invention provides a image forming device comprising: an interface adapted to communicate with a communication medium; imaging circuitry configured to consume a plurality of imaging consumables to form
20 hard images; a plurality of sensors configured to monitor respective statuses of the imaging consumables; and processing circuitry coupled with the sensors and configured to generate a composite message indicating statuses of the imaging consumables, and to forward the composite message to the interface for communication externally of the image forming device.
25

Another aspect of the invention provides a method of facilitating ordering of an imaging consumable comprising: providing an image forming device
30 configured to use the imaging consumable to form hard images; monitoring a status of the imaging consumable; generating a message indicating the status of the

imaging consumable responsive to the monitoring; synchronizing with another image forming device; and communicating the message externally of the image forming device responsive to the synchronizing.

Yet another aspect of the present invention comprises a method of facilitating ordering of an imaging consumable comprising: providing an image forming device configured to use the imaging consumable to form hard images; monitoring a status of the imaging consumable; generating a message indicating the status of the imaging consumable responsive to the monitoring; and communicating the message externally of the image forming device at a predetermined moment in time. Other aspects of the present invention are disclosed herein.

Other features and advantages of the invention will become apparent to those of ordinary skill in the art upon review of the following detailed description, claims, and drawings.

DESCRIPTION OF THE DRAWINGS

Fig. 1 is an isometric view of an exemplary image forming device embodying aspects of the present invention.

Fig. 2 is an illustrative representation of an exemplary image forming system embodying aspects of the present invention.

Fig. 3 is a functional block diagram of an exemplary image forming device.

Fig. 4 is a flow chart depicting an exemplary methodology executable within the image forming device.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Fig. 1 depicts an exemplary image forming device 10. Image forming device 10 is configured to form hard images upon media 12 in the described embodiment. One exemplary image forming device 10 comprises a printer, such as a laser printer, ink jet printer, a dot matrix printer, or a dry medium printer. The present invention is embodied within other image forming device configurations

such as multiple function peripheral devices, copiers, facsimile machines, plotters, etc. or other arrangements configured to form hard images upon media 12 according to alternative embodiments of the invention. Device 10 is arranged to form hard images upon media 12 including, for example, paper, envelopes, transparencies, labels, etc.

Referring to Fig. 2, an image forming system 11 is depicted comprising plural image forming devices 10, plural host devices 14 and a communication medium 16. Communication medium 16 provides connectivity intermediate image forming devices 10 and host devices 14 to implement communications therebetween. An exemplary communication medium 16 includes packet switched networks such as an Intranet network (e.g., Ethernet arrangement), Internet and/or other communication configurations operable to provide electronic exchange of information between image forming devices 10 and host devices 14, using an appropriate protocol, such as TCP/IP. Some of depicted devices 10, 14 of system 11 may be coupled with an Intranet portion of medium 16 while other devices 10, 14 are coupled with an Internet portion of medium 16. Other image forming systems 11 of the invention include more or less devices 10, 14 depending upon a given configuration or application. Further, other arrangements of communication medium 16 and other protocols for implementing communications intermediate devices 10, 14, are possible.

In general, host devices 14 are implemented as personal computers (PCs), servers, or other devices configured to communicate with image forming devices 10. Host devices 14 individually include a display 15, such as a CRT or flat panel monitor, to display information to a user.

At least some host devices 14 execute applications wherein formation of hard images upon media is desired. For example, host devices 14 comprising personal computers in one exemplary configuration execute an appropriate word processor, spread sheet, or other application capable of generating documents having images thereon. Individual host devices 14 communicate image data via communication medium 16 to an appropriate image forming device 10 for hard imaging. Alternatively, image data to be printed or otherwise imaged using image

forming devices 10 is supplied from other external devices (not shown) coupled with, for example, communication medium 16.

Referring to Fig. 3, exemplary components of a single image forming device 10 are shown. As illustrated, the depicted image forming device 10 includes a clock 18, storage circuitry 20, processing circuitry 22, imaging circuitry 24, a sensor 26, a sensor 27, and an interface 28 individually coupled with a communication medium 30. Communication medium 30 is configured as an internal bus to implement communication functionality intermediate components of image forming device 10. Other configurations of image forming device 10 are provided in alternative arrangements (not shown).

Clock 18 is arranged to provide information regarding current moments in time. For example, clock 18 provides year, month, day and/or time information. In the depicted configuration, clock 18 is programmed upon installation within system 11. Updated timing information to verify the accuracy of clock 18 or to control timing within device 10 may be received from a timing source (not shown) external of image forming device 10.

Storage circuitry 20 is configured to store instructions for controlling various operations of image forming device 10 and other information or data as described in further detail below. Exemplary storage circuitry 20 comprises non-volatile memory (e.g., EEPROM, flash memory and/or read only memory (ROM)), random access memory (RAM), and hard disk and associated drive circuitry. Storage circuitry 20 is configured to store executable instructions as firmware or software configured to control operations of image forming device 10. Further, storage circuitry 20 stores image data used for the formation of hard images and any other appropriate information to be stored within image forming device 10.

Processing circuitry 22 is implemented as a dedicated microprocessor in the depicted embodiment of image forming device 10. Other arrangements of processing circuitry 22 are possible. Processing circuitry 22 is configured to execute a plurality of ordered executable instructions implemented as firmware and/or software. The ordered instructions are executed to control image forming operations within image forming device 10, to provide monitoring of components

Imaging circuitry 24 is configured to form hard images upon media 12 responsive to image data. In the described printer embodiment, imaging circuitry 24 includes print circuitry arranged to print images upon media 12. In the exemplary described embodiment, imaging circuitry 24 includes paper path components (not shown) to implement movement of media 12 within image forming device 10, developing components (not shown) configured to provide a developing material, such as toner, upon media 12, fusing components (not shown) configured to affix the developing material to media 12 as well as any other components (not shown) to implement other desired processing or imaging operations, such as downstream processing of media (e.g., stapling, collating, etc).

In the described embodiment, sensors 26, 27 are arranged to monitor respective statuses of plural imaging consumables. Status of an imaging consumable may be represented in a plurality of ways. For example, sensors 26, 27 are arranged in one embodiment to monitor remaining capacities of respective imaging consumables (e.g., amount of toner in weight or volume remaining for usage, amount of fuser life in hours remaining for usage). Alternatively, sensors 26, 27 are configured to monitor usage of the respective imaging consumables. Sensors 26, 27 may be additionally configured to indicate both remaining capacity and usage of respective consumables. The remaining capacity and/or usage

Sensors 26, 27 are configured to output respective signals indicative of the statuses (e.g., usage and/or remaining life) of imaging consumables to communication medium 30. Processing circuitry 22 is configured to receive and process the respective signals from medium 30.

According to aspects of the present invention, image forming device 10 is operable to implement various functions regarding usage of imaging consumables during imaging and other operations, and replenishing of such imaging consumables. As previously mentioned, sensors 26, 27 are arranged to monitor statuses of respective imaging consumables. Sensors 26, 27 output signals indicative of the statuses of the respective imaging consumables.

Image forming device 10 arranged according to aspects of the present invention assists a user (e.g., purchaser or other desired entity concerned with maintenance of consumables) with replenishment of imaging consumables responsive to signals received from sensors 26, 27. Image forming device 10 is operable to output an indication of the statuses of respective imaging consumables externally of device 10 using interface 28.

More specifically, and in one exemplary configuration, processing circuitry 22 receives the generated signals regarding statuses of imaging consumables from respective sensors 26, 27. Processing circuitry 22 formulates messages which are forwarded externally of device 10 to appropriate recipients for

facilitating reordering of imaging consumables. As described below, exemplary messages generated by processing circuitry 22 include status messages identifying the imaging consumable and/or the status of the imaging consumable of device 10. Alternatively, processing circuitry 22 generates a composite message regarding the identification and/or statuses of plural imaging consumables, and/or a composite message regarding plural statuses of one imaging consumable and perhaps an identification of the imaging consumable.

In one implementation, one of the provided host devices 14 of system 11 is associated with a purchaser of imaging consumables for respective ones of image forming devices 10 or other described recipient. In such a configuration, an e-mail address, uniform resource locator (URL) or other identifier of such host device 14 is provided within storage circuitry 20 of respective image forming devices 10 which are monitored by the purchaser or recipient.

Following an indication from sensors 26, 27 of one or more imaging consumable being at a predetermined status (e.g., low remaining capacity), processing circuitry 22 formulates an appropriate message for application to the given host device 14 as identified by the identifier stored within storage circuitry 20. In the depicted embodiment, processing circuitry 22 configures messages as e-mail messages for communication using communication medium 16. Other formats of messages are possible.

In another arrangement, processing circuitry 22 formulates an appropriate message indicating status(es) of imaging consumable(s) without such status(es) having reached any predetermined status(es). Such provides updates of status(es) of respective imaging consumables.

According to aspects of the present invention, one or more image forming device 10 of image forming system 11 is configured to synchronize with one or more other device 10 to control timing of communication of messages regarding status(es) of one or more imaging consumable to the proper host device 14. In one configuration, processing circuitry 22 is configured to detect a predetermined moment in time as provided by clock 18 to synchronize with one or more other image forming device 10.

5

10

20

25

30

5

10

15

20

25

30

purchaser).

Processing circuitry 22 proceeds to a step S12 if the condition of step S10 is negative. At step S12, it is determined whether one or more of imaging consumables being monitored by sensors 26, 27 are at a predefined status (e.g, remaining capacity is low). If the condition of step S12 is negative, processing circuitry 22 returns to step S10.

Alternatively, if the condition of step S12 is affirmative, processing circuitry 22 proceeds to a step S14 to determine whether the imaging consumable having the status indication as determined by step S12 has already been added to a list. If so, processing circuitry 22 returns to step S10.

Otherwise, processing circuitry 22 proceeds to a step S16 to add the imaging consumable having the status indication to a list stored within storage circuitry 20. Thereafter, processing circuitry 22 returns to step S10.

If the condition of step S10 is in the affirmative, processing circuitry 22 proceeds to a step S18 to forward a composite message including the imaging consumables on the list stored within storage circuitry 20. The composite message is forwarded to interface 28 for communication to medium 16 and appropriate host device 14 or other appropriate destination.

Thereafter, and at a step S20, processing circuitry 22 clears the list within storage circuitry 20 and returns to step S10.

Aspects of the present invention provide forwarding of status messages from a plurality of image forming devices 10 to a host device 14 associated with a purchaser of imaging consumables, or other responsible individual, at predetermined moments in time.

Other aspects of the present invention include providing a composite message regarding statuses of one or more imaging consumable for communication to the appropriate host device 14. Such facilitates compilation by the purchaser or other individual of a plurality of imaging consumables to be ordered for one or more of image forming devices 10.

The purchaser or other individual reviews status messages received at the predetermined moment in time from the associated image forming devices

10 to compile the purchase order for imaging consumables. Such eliminates the steps of having the purchaser locate, retrieve and tally all status messages sent since the last purchase order during compilation of the next purchase order. Provision of composite messages according to other aspects of the present invention eliminates the steps of having the purchaser or other individual locate and tally numerous individual status messages which may be communicated from a single image forming device 10 during a given time period.

The protection sought is not to be limited to the disclosed embodiments, which are given by way of example only, but instead is to be limited only by the scope of the appended claims.

0033794.121300